

Termostaty RANCO



Typ	Prac. rozsah	Diferencia	Kapilára	Hmotnosť	Pozn.
016-H-6900	-35°C -7°C	1,0-1,5K	priest.	450	
016-H-6901	-18°C +13°C	1,0-1,5K	priest.	450	
016-H-6906	-5°C +25°C	1,0-6,0K	Priest.	450	
016-H-6930	-30°C +32°C	3,0-22K	kap. 1800 mm	550	Ø9,5
016-H-6958	-35°C -7°C	1,7-12K	kap. 2000 mm	450	špirála
016-H-6959	-15°C +15°C	1,7-12K	kap. 2000mm	450	špirála
016-H-6981	-5°C +25°C	1,7-12K	kap.1800mm	680	Ø4,5
016-H-6924	-5°C +25°C	1,7-12k	kap.2000mm	450	kapilára
016-H-6921	-40°C -7°C	1,7-12K	kap.2000mm	450	kapilára
016-H-6983	+10°C +40°C	1,7-15K	kap.1800mm	680	Ø4,5

Poznámky:

elektrické krytie IP 30, s krytom IP 44
 kontakty 1-4 rozpína a 1-2 spína pri stúpaní teploty, hlavné kontakty 16A

Termostaty 052 a 016



282.2333	O 16-6921 -40/-7 kap.
282.2336	0-16-H6924
282.2338	O 16-6930 -30/+32 kap.
282.2346	O 16-6958 -35/-7 kap.
282.2347	O 16-6959 -18/+13 kap.
282.2351	O 16-6983 +10/+40 kap.
282.2355	O 16-6900 -35/-7 priest.
282.2356	O 16-6901 -18/+13 priest.
282.2361	O 16-6906 -5/+25 priest.